



OKI

A new era in flexible label printing

Pro1040 + Pro1050 Label Printers

The Pro Series Label Printer takes creativity and flexibility to a new level, offering professional four (Pro1040) and five-colour (Pro1050) narrow-format printing across a range of materials. Launching on-demand, short-run colour label printing services opens the door to a new customer base, as well as a lucrative revenue stream.

Bringing a new colour dimension to printed labels

Using digital LED technology together with dry toner technology, the fifth colour or 'CMYK+1' option, allows for greater flexibility in your label design. Printing on transparent or coloured label media is now straightforward by printing an opaque white background under the CMYK image. Your printed label stands out even more, ensuring your message is always clear.



Versatile professional label printing for labels with impact

With unrivalled media handling capability, printing on a huge range of media, from textured papers and synthetics, with white, clear, opaque or coloured substrates, is easier than ever. The Pro Series Label Printer handles with ease new types of materials that inkjet label printers simply can't, so businesses can take on creative ideas and complex job types. Whether it's outdoor use labels, freezer and cold-storage labels, or food, beverages and household goods, the Pro Series can deliver them all.



Printed labels as a profitable on-demand service

It's time to stop giving profit away to your competitors. The Pro Series Label Printer requires minimal training, has flexible configuration and offers internal printing capability across a wide range of tasks. Set up new jobs in minutes. Print on coated and uncoated paper or synthetic media, and use just one printer for multiple jobs. OKI's Pro Series Label Printer is ideal for short to medium run label production.



Labels that are robust, waterproof and UV resistant

The Pro Series Label Printer can be used to produce waterproof labels that have been tested to survive underwater, and are robust and resistant to UV fading. Ideal for industrial chemical labelling and asset tracking.



Making great ideas **STICK**

Pro1040 & Pro1050 Printer Specifications

Specification summary ¹	Pro1040 & Pro1050
Colour Options	Pro1040 (CMYK) & Pro1050 (CMYK + W)
Media Type ²	Plain Paper, Film, Plain Paper Label, Glossy Paper Label, Synthetic Film Label
Media Width	Roll paper: 25.4mm(1.0")- 130mm (5.1") including liner
Media Thickness	0.076 - 0.250mm
Label Length per job	12.7mm (0.5") - 1320.8mm (52")
Print Width	21.16mm(0.83") - 125.76mm(4.95")
Media Detection	Black Mark (printed on back of liner), Gap, None
Media Format	Roll
Roll Outer Diameter / Core Inner Diameter	Max. Φ 203.2mm (Φ 8") / Φ 76.2mm (Φ 3")
Roll Wind Direction	Face-out, Face-in
Minimum Print Margin	Top: 2.12mm, Bottom: 2.12mm, Right: 2.12mm, Left: 2.12mm
Print Position Accuracy / Cut Accuracy	Vertical: \pm 0.5mm, Horizontal: \pm 0.5mm / Vertical: \pm 0.5mm
Cut Length	Min. 101.6mm(4")
Print Resolution	1200 x 1200 dpi, 600 x 600 dpi
Print Speed	Max. 152.4mm/s (6ips)
Interface	1000BASE-T / 100BASE-T / 10BASE-T, High-speed USB2.0
Protocol	TCP/IP
Printer Language	Adobe PostScript ³ , PCL 5c emulation, PCL 6 (XL) emulation
Supported OS ⁴	Windows10, Windows8.1, Windows8, Windows7, Windows Server 2016, Windows server 2012 R2, Windows server 2012, Windows Server 2008 R2, Windows Server 2008
Processor Speed	ARM 1.2 GHz
Memory (Std./Max)	2,000 MB / 2,000 MB
Hard Disk Drive	250 GB
Font	Adobe PostScript 136 fonts, PCL emulation 81 scalable fonts, 4 bitmap fonts
Auto Cutter	Rotary blade full cut
Dimensions	1040(D) \times 477(D) \times 441(H) printer with unwinder
Weight	Approx. 61kg (Pro1040) / Approx.62kg (Pro1050) (including consumables) Approx. 50kg (without consumables)
Operating Environment	Operating: 10 - 30 °C, 20 - 70 %RH, Storage: -10 - 43 °C, 10 - 90 %RH, No condensation
Power Source	Single phase 230V AC \pm 10%, 50/60 Hz \pm 2%
Power Consumption	Operating: Max. 1200W / Ave. 710W, Idle: 27W w/o rewinder, Power Save: 25.0W
Safety & Environment	RoHS, Network Access License, cUL Mark, cULus Mark, UL Mark, CSA Mark, EMC-Directive, CE Mark, GS Mark
Toner / Image Drum Life (C,M,Y,K)	9K Pages (A6 20% coverage each colour)
Toner / Image Drum Life (W)	4.5K Pages (A6 20% coverage)
Transfer Belt / Fuser Life	150K Pages (approx 40km of labels @A6 pages)
Waste Toner Box Life	25K Pages
In The Box	Manuals, Power cable, DVD-ROM (Software Drivers & BarTender® UltraLite)

¹Specification subject to change without notice. All trademarks acknowledged.

²Media list available (all media should be pre-tested before ordering in quantity).

³Available in 2018 after product launch.

⁴Windows10, Windows8.1, Windows8, Windows7 and Windows Server 2008 are compatible with 32 bit and 64 bit.



OKI Pro1040



OKI Pro1050





OKI Data Australia Pty. Ltd.
Level 1, 67 Epping Road
Macquarie Park, NSW 2113
Australia
T 1800 800 140
www.oki.com/au

OKI

Open up your dreams

© Copyright 2018 OKI Data Australia Pty. Ltd. OKI Data Australia Pty. Ltd. is part of the OKI Electric group of companies. Specifications subject to change without notice. All trademarks acknowledged. Version 2.1 03/2020.



-  digital printers
-  thermal printers
-  weighing scales
-  labels & support

QLM Label Makers Sdn Bhd

No. 7, Jalan TPP 6/6, Taman Perindustrian, Puchong 6, 47100 Puchong Selangor
p +603 8062 7823 e malaysia@qlmgroup.com

Three-P Systems Sdn Bhd

No 13-1, 1st Floor, Jalan Mahkota Residence 1,
Bandar Mahkota Cheras, 43200 Cheras, Selangor.
p +603 9011 6866 e info@3psystems.my

qlm.com.my 3psystems.my